



Box 506, Cochrane, AB T4C 1A7
Phone: 403-208-9733 • Fax: 403-208-9743

RIG # 47

CARRIER:	HWSS 400-72
CAPACITY:	2500 m
DRAWWORKS:	38 x 10" DD c/w 38 x 8" SD (7/8" Drill line, 9/16" Sandline)
DERRICK:	140,000lb Static Hook Load Free Standing (4 lines) 170,000lb c/w Crown Lines. 72' Hyduke Stiff Mast Tbg board 2500m x 2 7/8", Rod board 2500m x 7/8"
POWER:	425hp Series 60 Detroit Diesel 750 / 5 speed Allison Automatic transmission Tri-Drive / Tandem steering
FALL PROTECTION:	2 fall arrest posts engineered to 5000 lb capacity located at the crown
B.O.P's:	Schaffer Sentinel II 7 1/16"x 35mPa c/w kill spool
ACCUMULATOR:	33 Gallon class III c/w N2 backup
POWER TONGS:	Foster 58/93 "R" c/w air backup
ROD TONGS:	Oil Country 5/8 – 1" equipped c/w backup
SLIPS:	100 Tonne Cavin model "C" (2 3/8 – 3 1/2")
PUMP:	Oilwell P-110 c/w 7 valve x 21mPa manifold
TANK:	28m3 capacity c/w Degasser, Mixing jet's & sample trough
CHANGE SHACK:	Office/ Tool Room c/w Incinerlet facility. 42 KW (continuous power) Kubota generator 33 gallon backup class III accumulator system
RIG MOVES:	Totally Mobile